

Resilient & Sustainable Power Protection



centiel
continuous power availability

Premium Tower™ S2

Empowering a Resilient Sustainable Future
Three-phase UPS 10-80kW





Empowering a Resilient Sustainable Future

PremiumTower™ S2 is Centiel's next-generation of resilient eco-responsible three-phase UPS solution, crafted to help organizations protect their critical loads while actively reducing their carbon footprint. With PremiumTower™ S2, you demonstrate a commitment to both cutting-edge resilience and planetary well-being.

Advanced Performance

High reliability by design

Three independent power converters increase system reliability and provide power continuity even in cases of power component failure.

Market leading charging current

With the ability to provide up to 5 times more charging current than typical standalone, PremiumTower™ S2 reduces the total system cost by eliminating the need for external battery chargers.

Short circuit capability


With a Short Circuit capability of 3 times nominal current ($3 \times I_n$), PremiumTower™ S2 is able to clear output circuit protection in milliseconds.

Class-Leading Efficiency

With an ultra-efficient architecture achieving up to 97.1% efficiency in double conversion PremiumTower™ S2 push the boundaries of eco-sustainability.


Lowest Total Cost of Ownership

Efficiency
VFI
Up to **97.1%**



Zero waste for a Greener Planet

PremiumTower™ S2 market leading ultra-efficient architecture of up to 97.1% efficiency in double conversion, and no replaceable components for 15+ years reduce the energy consumption, lowering heat dissipation and cutting operating expenses. As a result, fewer resources are needed further shrinking your environmental impact.



Based on 20kW 10min autonomy. Cooling energy based on EER=3
0.219 €/kWh Euro area average
Source EUROSTAT

Maximized Flexibility



Flexible battery blocks

The flexibility in the number of battery blocks (17 to 50), eliminates the need to oversize the batteries and allows system designers to optimize cost versus autonomy time.

Integrated autonomies and matching battery cabinets

Up to 240 battery blocks can be fitted in the PremiumTower™ S2 10 to 80 kW, reducing the total footprint and optimizing costs. For higher ratings and extended runtime, matching battery cabinets are available.

Dual or single input feed

PremiumTower™ S2 can be supplied with two independent AC sources to further increase the power availability of the installation.

Compatible with different battery technologies

Lead acid, Gel, NiCd, Flywheels, Lithium and other types of energy accumulators can be used with PremiumTower™ S2.

17^{to} 50 Flexible Battery Blocks
LITHIUM READY

| Unbeatable Efficiency 97.1%

| Increased nominal rating
(kW = KVA)

| 15+ years life on replaceable components

| Smart-predictive fans

| Backfeed Protection
(Standard)

| 500% higher charging current than typical standalone UPS

| Up to 80kW with internal batteries

Power density Up to

181 kW/mq

80 kVA

8 min

0.44 m²



Non-intrusive maintenance

Minimized maintenance and repair time contribute to keeping the systems' high availability.

Smart-Predictive Fans

With its closed-loop control system PremiumTower™ S2 actively monitors fans usage and detect signs of degradation alerting users at exactly the right time to replace components, ensuring ongoing reliability and eliminating unnecessary maintenance costs.

User-friendly display

The display and LED interface simplifying user interaction give immediate visibility to the status of the UPS.

15+ Years

Designed to deliver a service life of 15+ years in components. Beyond reliability, this longevity actively reduces waste and costs from parts replacement.

Remote monitoring

Graphical display

Generator operation mode

Auxiliary contacts

5 Dry Contacts and 5 Digital Inputs

Standard

Standard programmable input and output

Dry contacts

Compensated battery charging

Temperature probe

SNMP, Modbus, ModBus over IP

Slide-in adaptors

Simplified service

USB and Bluetooth app

Tangible sustainability:

PremiumTower™ S2 means supporting a commitment to preserve natural resources, cut operational costs, and create a positive environmental impact. It is an investment in a future where businesses thrive while reducing their ecological footprint.



Energy efficiency

PremiumTower™ S2 is designed with energy efficiency in mind, using the latest technology to reduce energy consumption and minimise losses.

97.1% (VFI) efficiency

Zero waste

PremiumTower™ S2 is manufactured using eco-friendly materials, ensuring that our products have minimal impact on the environment.

15+ years of life on replaceable components

Net zero by design

Centiel is continuously committed to improving our sustainability practices, and we manufacture PremiumTower™ S2 using environmentally friendly processes to minimize our impact on the environment.

96% of the energy used for production testing is recycled and renewable

Tower D1




Footprint 0.29m²

Tower D0



Footprint 0.29m²

Tower E0



Footprint 0.44m²

Model	kVA/kW	Int. Batt.
UPS2-PT010-I080-D1	10	80
UPS2-PT020-I080-D1	20	80

Model	kVA/kW	Int. Batt.
UPS2-PT010-I120-D0	10	120
UPS2-PT020-I120-D0	20	120
UPS2-PT030-I120-D0	30	120
UPS2-PT040-I120-D0	40	120
UPS2-PT060-E-D0	60	
UPS2-PT080-E-D0	80	

Model	kVA/kW	Int. Batt.
UPS2-PT010-I240-E0	10	240
UPS2-PT020-I240-E0	20	240
UPS2-PT030-I240-E0	30	240
UPS2-PT040-I240-E0	40	240
UPS2-PT060-I240-E0	60	240
UPS2-PT080-I240-E0	80	240

PremiumTower™ S2	Cabinet Type			Internal batteries	Autonomy min
10kVA	D1	Do	Eo		
UPS2-PT010	Max 80 batteries		n/a	Ext. Batt.	-
UPS2-PT010				1 x 7	11
UPS2-PT010		Max 120 batteries		1 x 9	16
UPS2-PT010				2 x 7	28
UPS2-PT010				2 x 9	45
UPS2-PT010	Max 240 batteries			3 x 7	52
UPS2-PT010				3 x 9	70
UPS2-PT010			5 x 7	91	
UPS2-PT010			5 x 9	118	
UPS2-PT010			6 x 9	153	
20kVA	D1	Do	Eo		
UPS2-PT020	Max 80 batteries		n/a	Ext. Batt.	-
UPS2-PT020				1 x 9	6
UPS2-PT020		Max 120 batteries		2 x 7	11
UPS2-PT020				2 x 9	16
UPS2-PT020				3 x 7	19
UPS2-PT020	Max 240 batteries			3 x 9	28
UPS2-PT020				5 x 7	42
UPS2-PT020			5 x 9	56	
UPS2-PT020			6 x 9	72	

PremiumTower™ S2	Cabinet Type		Internal batteries	Autonomy min
30kVA	Do	Eo		
UPS2-PT030	Max 120 batteries	n/a	Ext. Batt.	-
UPS2-PT030		Max 240 batteries	2 x 7	6
UPS2-PT030			2 x 9	9
UPS2-PT030			3 x 7	12
UPS2-PT030			3 x 9	16
UPS2-PT030			5 x 7	23
UPS2-PT030			6 x 7	29
UPS2-PT030			6 x 9	33
40kVA	Do	Eo		
UPS2-PT040	Max 120 batteries	n/a	Ext. Batt.	-
UPS2-PT040		Max 240 batteries	2 x 9	5.5
UPS2-PT040			3 x 7	7
UPS2-PT040			3 x 9	11
UPS2-PT040			5 x 7	15
UPS2-PT040			6 x 7	20
UPS2-PT040			6 x 9	28
60kVA			Do	Eo
UPS2-PT060	Max 240 batteries	n/a	Ext. Batt.	-
UPS2-PT060		3 x 9	6	
UPS2-PT060		4 x 9	10	
UPS2-PT060		6 x 9	16	
80kVA	Do	Eo		
UPS2-PT080	Max 240 batteries	n/a	Ext. Batt.	-
UPS2-PT080		5 x 9	6	
UPS2-PT080		6 x 9	8	

Technical Datasheet - From 10 to 80 kVA/kW

		Model	UPS2-PT010- I080-D1 UPS2-PT010- I120-Do UPS2-PT010- I240-Eo	UPS2-PT020- I080-D1 UPS2-PT020- I120-Do UPS2-PT020- I240-Eo	UPS2-PT030- I120-Do UPS2-PT030- I240-Eo	UPS2-PT040- I120-Do UPS2-PT040- I240-Eo	UPS2-PT060- E-Do UPS2-PT060- I240-Eo	UPS2-PT080- E-Do UPS2-PT080- I240-Eo	
General Data		Product name	PremiumTower™S2 UPS						
		Topology/Technology	Online double conversion						
		Max Power [kVA/kW]	10	20	30	40	60	80	
Input	Mains	Input Wiring	3Ph+N+PE						
		Rated Voltage	380/400/415Vac						
		Voltage Range	For loads < 100% (-25%, +20%) / < 80% (-32.5%, +20%) <60% (-35%, +20%)						
		Input Frequency	30-70 Hz						
		Total Harmonic Distortion	THDi <= 1% for nominal load						
		Input Power Factor	0,99						
	Bypass	Input Wiring	3Ph+N+PE						
		Rated Voltage	380/400/415 Vac						
		Change over tolerance	± 30... ± 10% (Voltage) (According to VFI-SS-111)						
		Input Frequency	50/60 ± 2/4% (selectable)						
	Battery	Rated Voltage	204-600 Vdc (the number of batteries can be selected)			276-600 Vdc (the number of batteries can be selected)			
		Type	Lead-Acid / NiCad / Lithium / Zink / Salt / others...						
		Internal batteries (7/9Ah)	I080: 80	I120: 120	I240: 240	I120: 120	I240: 240	E: External	I240: 240
		Blocks[VRLA]	17-50			23-50			
		Charger (Amp)	20	20	30	30	30	40	
Output	Inverter	Output Wiring	3Ph+N+PE						
		Nominal Power [kW]	10	20	30	40	60	80	
		Voltage	380/400/415 Vac ± 1%						
		Frequency	Tracking the bypass input (Online Mode); 50/60 Hz ± 0.1% (Battery Mode)						
		Waveform	Sine wave (THDv < 1%)						
		Output Power Factor	1						
		Efficiency	97.1 %						
		Overload Capacity	Inverter: 125% for 10 min, 150% for 60 sec Bypass: 135% for long term; <1000% for 100ms						
		Short circuit capability	Up to 3xIn						
	Bypass	Efficiency	99,4 %						
	Environment	Operating Temperature	0-40°C						
Storage Temperature		-40-70°C							
Relative Humidity		0%-95% (No condensing)							
Maximum Operating Altitude		1000 m. Above 1000 m, derating 1% for each additional 100 m							
Others	Dimensions (H x W x D) mm	D1 842 x 349 x 840 D0 1,077 x 349 x 840 E0 1,780 x 510 x 850		D0 1,077 x 349 x 840 E0 1,780 x 510 x 850		D0 1,077 x 349 x 913 E0 1,780 x 510 x 905			
	Weight without batteries[kg]	D1 67 D0 75 E0 120		D0 75 E0 120		D0 97 E0 177			
	Colour / protection level	RAL 9017 (traffic black) / IP20							
	Certifications	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 CE UKCA EAC RoHS							
	Communications	RS485, USB, Dry contacts, Ethernet, Bluetooth							

The information in this document is subject to change without notice and should not be construed as a commitment by Centiel S.A.
TDS_Rev01-CW_Rev01